



Fitch Fuel Catalyst c/o
 Advanced Power Systems Inc
 339 Main Street
 Torrington, CT 06790
 888-881-2774

Fitch Fuel Catalyst Heavy Duty Engines



Features/Specs

- Die-cast aluminum head
- Steel bowl assembly
- Viton "O" ring seal
- 1 1/2" NPT Thread
- Black Powder coated components
- "Locking ring collar" – no V-clamps
- Designed to withstand 150 PSI
 Maximum pressure at 250 deg. F
- Manual drain valve
- Manual vent valve
- Warranted for 10,000 operating hours
- Head dimension 8" x 8"



Part	Dimensions	Inlet/outlet	Weight
	<u>L x Diam</u> <u>inches</u>	<u>fitting size</u>	<u>Lbs</u>
FHD5-19-1.5	18.8 X 6.48	1 1/2 NPT	26.6
FHD10-38-1.5	18.8 X 6.48	1 1/2 NPT	33.7
FHD15-57-1.5	18.8 X 6.48	1 1/2 NPT	40.6
FHD20-76-1.5	22.8 X 6.48	1 1/2 NPT	45.0
FHD25-95-1.5	22.8 X 6.48	1 1/2 NPT	52.0

Part	Diesel/ Bio-diesel		Heavy Oil		Propane	
	<u>GPM</u>	<u>LPM</u>	<u>GPM</u>	<u>LPM</u>	<u>GPM</u>	<u>Kg/ M</u>
FHD-5-19-1.5	5	19	4	13	4.4	489
FHD-10-38-1.5	10	38	7	26	8.7	979
FHD-15-57-1.5	15	57	11	40	13.1	1,468
FHD-20-76-1.5	20	76	14	53	17.4	1,958
FHD-25-95-1.5	25	95	18	66	21.8	2,447

**M = Minutes